



Lighting System - PlassLED



Features

- Lighting system designed for livestock applications.
- High efficiency and durability.
- Easy programming and controlling of all lighting aspects.
- Modular system for flexibility during installation.
- Operation modes: manual or through the house controller.
- No flickering - when DC drivers are used, even at very low capacity.

Technical Data

- Lamp size (approx.) - 300X30X5mm
- Garland lengths - 40m (10 lamps), 20m (5 lamps)
- Spacing between lamps - 4m
- Voltage – 220/240 Volt AC/DC (dimnable)
- Power (dimnable) - 0.5-15W

Driver & Lamps

DIMMING DRIVER KIT

0-10V 1.5KW

02387163

Units per box: 1



LIGHTING GARLAND DIM 13W

IP65 M/F

02387161 - 40m, 10 Lamps,

6 Units per Box

02387162 - 20m, 5 Lamps,

12 Units per Box



SINGLE LAMP DIM LED 13W IP65

2700K

02387166

Units per box: 60



- Protection rate - IP65
- Efficiency - 150 Lumen/W
- Luminosity - Up to 1900 Lumen
- Lamp temperature range – 2700-5700K
- Beam angle - 170°

Connectors

FEMALE CONNECTOR IP68

02387164

Units per box: 120



2 WAY CONNECTOR IP68

02387165

Units per box: 20



3 WAY "T" CONNECTOR IP68

02387167

Units per box: 20



Suspension

Ceiling

PHILLIPS TRUSS HEAD SCREW

PIERCING POINT 4X16mm

02382248



COATED STEEL ELECTRIC CABLE

HANGER 6mm

02382454



By Cable

GALVANIZED EYE & HOOK TURN

BUCKLES 8mm

02312567



WALL CONNECTION PLATE

FOR INLET COUNTER SPRING

02381003



GALVANIZED LIGHT DUTY

THIMBLES 3-7mm

02312568



GALVANIZED CARBIN SNAP

HOOK 8X80mm

02381173



CABLE CLAMP 3/16"

02310023



DOUBLE HOOK FOR METAL

HOUSE COM.

02312004



STEEL CABLE 3/16" (Per meter)

02320002



PLASTIC STRAP 310X4.8mm

BLACK

02312542



Feeding



Drinking



Climate



Housing

Maagan Michael, D.N. Menashe, 3780500, Israel • Tel: +972-73-241300 • Fax: +972-73-2333711 • info@plassonlivestock.com

WWW.PLASSONLIVESTOCK.COM